



### Key Features

- Noise-free cellar environment
- Operates in extreme environments
- Simple installation - between wall studs
- Remote Advanced electronic control system w/ 50ft. communication line
- Liquid bottle probe
- Humidity control
- Energy saving mode
- 55°F temperature differential



### Features

The Fully Ducted Extreme Series units can be positioned up to 25 ducted feet from the cellar, creating a noise-free cellar environment. Fully ducted installation provides many installation options, allowing you to not only put the unit in more remote areas of the home but to also have full control of where the exhaust air vents to. This series features an advanced liquid temperature controller with a remote LED display (which can be placed up to 300 line feet from the unit) and electronic thermostat. Maintain 55°F and 50-70% relative humidity in a cellars up to 1000 cu. Ft. (5000tiR) or 2000 cu. Ft. (8000tiR) in size.

### Specifications

Model	5000tiR	8000tiR
Cellar Size	1000 cu. ft.	2000 cu. ft.
Dimensions	14.25" W x 15.75" H x 28" D	14.25" W x 22" H x 28" D
Weight	96lbs	110lbs
AMPS (starting/running)	32/9	36/10
Installation	Through-the-Wall, partially ducted, fully ducted	
Thermostat	Digital Control Display	
Temp. Delta	55°F temperature differential (maintains proper cellar temperature when exhaust environment does not exceed 110°F)	
Outside Venting	Can be done if the outside temperature does not exceed 110°F, the external grille cover is highly recommended.	
Ducting Options	Unit can be fully ducted.	
Warranty	2 year parts and labor / 5 year compressor	
Compliance	ETL Listed	

### Optional Accessories

Ducting Plenum, Exterior Grille